

# Emperor Masonry Primer



A water-based primer for bare, unpainted masonry surfaces before applying Emperor Masonry Paint.

**Application:** Applied using a paint brush, paint roller or airless sprayer. A minimum temperature of 5°C is required.

**Recommended For:** Apply Emperor® Masonry Primer on normal absorbent surfaces.

**Colour:** Milky White

**Coverage Rate:** 5-8 m<sup>2</sup> per litre, depending on porosity.

**Pack Sizes:** 5L and 10L containers.

**Drying Time:** 3-5 hours at 20°C. Lower temperatures and higher humidity extend the drying time accordingly.

**Equipment Care:** Clean in water directly after use.

**Storage:** Protect from direct sunlight, heat sources and frost. Keep opened container tightly sealed.

**Shelf Life:** 12 months (in original sealed container).

**Safety:** In accordance with current labelling non-hazardous content. More information regarding precautions can be found on the product label or on the manufacturer's safety data sheet.



\*when applied in accordance with the manufacturer's datasheet

**Declare.**

[www.emperorpaint.co.uk](http://www.emperorpaint.co.uk)

Unit 1  
Syke Side Drive  
Altham Industrial Estate  
BB5 5YE  
United Kingdom  
[info@emperorpaint.co.uk](mailto:info@emperorpaint.co.uk)

**Tested & approved by the world's leading scientists**