

Emperor Textured Basecoat



An exterior textured coating for creating a range of textured finishes on exterior rendered surfaces.

Recommended For: Any bare or previously painted masonry and render, including brick, stone, cement and render, where a textured finish is required.

Preparation: All surfaces must be dry, clean, sound and free of contaminants. Cracks and holes greater than 0.5mm need to be repaired with a suitable masonry filler. Allow any filler to dry thoroughly for minimum 24 hours. Emperor Textured Basecoat is self-priming and does not require a primer.

Application: Thoroughly stir before use. Apply using a paint brush or paint roller. Using either a light, medium or rough textured roller will help create different finishes. Apply generously with a full brush or roller and avoid spreading too thinly. Once applied and left to dry, overcoat using a masonry paint of your choice.

Colour: White

Coverage rate: Approx. 350–500 g/m² per coat when creating a light texture. The heavier the texture, the lower coverage rate.

Drying time: Touch dry in up to 4 hours 20°C. Recoatable in 24 hours at 20°C. Lower temperatures and higher humidity extend the drying time accordingly.

Application Conditions: Minimum temperature 5°C. Relative humidity should not exceed 65%.

Storage: Must be stored in dry, frost free conditions preferably at room temperature.

Shelf life: Minimum 2 years (in original sealed container).

Cleaning: Clean equipment with warm soapy water.



*when applied in accordance with the manufacturer's datasheet

Declare.

www.emperorpaint.co.uk

Unit 1
Syke Side Drive
Altham Industrial Estate
BB5 5YE
United Kingdom
info@emperorpaint.co.uk

Tested & approved by the world's leading scientists